


Insulated Terminal




**KC-8A**  
For Insulated Terminal & Connector  
AWG 20-18/16-14/12-10  
0.5-1.0/1.5-2.5/4.0-6.0 mm<sup>2</sup>



**KC-8A1**  
For Insulated Terminal & Connector  
AWG 22-18/16-14/12-10/8  
0.5-1.0/1.5-2.5/4.0-6.0/10 mm<sup>2</sup>



**KC-8A2**  
For Insulated Terminal & Connector  
AWG 20-18/16-14/12-10  
0.5-1.0/1.5-2.5/4.0-8.0 mm<sup>2</sup>



**KC-8A4**  
For Insulated Terminal & Connector  
AWG 26-20/18-16/14/12-10  
0.14-0.5/0.75-1.5/2.5/3.5-6 mm<sup>2</sup>



**KC-8A5**  
For Close End Terminal  
AWG 20-16/16-14/12-10  
0.5-1.5/1.5-2.5/4.0-6.0 mm<sup>2</sup>



**KC-8A6**  
For Close End Terminal  
AWG 12/10/8  
4/6/10 mm<sup>2</sup>

Ratchet Hand Crimping Pliers KC-8 Series

Model	For Terminal	Application Range		Weight Kg.	Length mm.
		mm <sup>2</sup>	AWG		
KC-8A	For Insulated Terminal & Connector	0.5-1.0/1.5-2.5/4.0-6.0	20-18/16-14/12-10	0.6	230
KC-8A1		0.5-1.0/1.5-2.5/4.0-6.0/10	22-18/16-14/12-10/8	0.6	230
KC-8A2		0.5-1.5/1.5-2.5/4.0-8.0	20-16/16-14/12-10	0.6	230
KC-8A4		0.14-0.5/0.75-1.5/2.5/3.5-6	26-20/18-16/14/12-10	0.6	230
KC-8A5	For Close End Terminal	0.5-1.5/1.5-2.5/4.0-6.0	20-16/16-14/12-10	0.6	230
KC-8A6		4/6/10	12/10/8	0.6	230

