


Insulated Terminal




KC-8A
For Insulated Terminal & Connector
AWG 20-18/16-14/12-10
0.5-1.0/1.5-2.5/4.0-6.0 mm²



KC-8A1
For Insulated Terminal & Connector
AWG 22-18/16-14/12-10/8
0.5-1.0/1.5-2.5/4.0-6.0/10 mm²



KC-8A2
For Insulated Terminal & Connector
AWG 20-18/16-14/12-10
0.5-1.0/1.5-2.5/4.0-8.0 mm²



KC-8A4
For Insulated Terminal & Connector
AWG 26-20/18-16/14/12-10
0.14-0.5/0.75-1.5/2.5/3.5-6 mm²



KC-8A5
For Close End Terminal
AWG 20-16/16-14/12-10
0.5-1.5/1.5-2.5/4.0-6.0 mm²



KC-8A6
For Close End Terminal
AWG 12/10/8
4/6/10 mm²

Ratchet Hand Crimping Pliers KC-8 Series

Model	For Terminal	Application Range		Weight Kg.	Length mm.
		mm ²	AWG		
KC-8A	For Insulated Terminal & Connector	0.5-1.0/1.5-2.5/4.0-6.0	20-18/16-14/12-10	0.6	230
KC-8A1		0.5-1.0/1.5-2.5/4.0-6.0/10	22-18/16-14/12-10/8	0.6	230
KC-8A2		0.5-1.5/1.5-2.5/4.0-8.0	20-16/16-14/12-10	0.6	230
KC-8A4		0.14-0.5/0.75-1.5/2.5/3.5-6	26-20/18-16/14/12-10	0.6	230
KC-8A5	For Close End Terminal	0.5-1.5/1.5-2.5/4.0-6.0	20-16/16-14/12-10	0.6	230
KC-8A6		4/6/10	12/10/8	0.6	230

