



Open Barrel Connector
(Non-Insulated Receptacle)



MADE IN TAIWAN



KC-8C

For Non-Insulated Receptacle
& Tab Terminal
AWG 20-18/16-14/12-10
0.5-1/1.5-2.5/4-6 mm²



KC-8C1

For precise machining
For Non-Insulated Receptacle
& Tab Terminal
AWG 20-18/16-14/12-10
0.5-1/1.5-2.5/4-6 mm²



KC-8C2

For Non-Insulated Receptacle
& Tab Terminal
AWG 24-18
0.25-1 mm²



KC-8C3

For Non-Insulated Receptacle
& Tab Terminal
AWG 26-22/20-18/16
0.14-0.25/0.5-1/1.5 mm²



KC-8C4

For Non-Insulated Receptacle
& Tab Terminal
AWG 26/18/16/14
0.14/1/1.5/2.5 mm²



KC-8C5

For Non-Insulated Receptacle
& Tab Terminal
AWG 22-20/18-16/14/12-10
0.25-0.5/1-1.5/2.5/4-6mm²

Ratchet Hand Crimping Pliers KC-8 Series

Model	For Terminal	Application Range		Weight Kg.	Length mm.
		mm ²	AWG		
KC-8C	For Non-Insulated Receptacle & Tab Terminal	0.5-1/1.5-2.5/4-6	20-18/16-14/12-10	0.6	230
KC-8C1		0.5-1/1.5-2.5/4-6	20-18/16-14/12-10	0.6	230
KC-8C2		0.25-1	24-18	0.6	230
KC-8C3		0.14-0.25/0.5-1/1.5	26-22/20-18/16	0.6	230
KC-8C4		0.14/1/1.5/2.5	26/18/16/14	0.6	230
KC-8C5		0.25-0.5/1-1.5/2.5/4-6	22-20/18-16/14/12-10	0.6	230

