



KC-8C48
For Non-Insulated Receptacle
& Tab Terminal
AWG 20-18/18-14/12-10
0.5-1.0/1.5-2.5/4.0-6.0 mm²



KC-8C63
For Non-Insulated Receptacle
& Tab Terminal
AWG 20-18/18-14/12-10
0.5-1.0/1.5-2.5/4.0-6.0 mm²



KC-8C448
For Non-Insulated Receptacle
& Tab Terminal
AWG 26/20/18/16/14
0.14/1.0/1.5/2.5 mm²

Ratchet Hand Crimping Pliers KC-8 Series

Model	For Terminal	Application Range		Weight Kg.	Length mm.
		mm ²	AWG		
KC-8C48	For Non-Insulated Receptacle & Tab Terminal	0.5-1.0/1.5-2.5/4.0-6.0	20-18/18-14/12-10	0.6	230
KC-8C63		0.5-1.0/1.5-2.5/4.0-6.0	20-18/18-14/12-10	0.6	230
KC-8C448		0.14/1.0/1.5/2.5	26/20/18/16/14	0.6	230



KC-8FL02
For Non-Insulated 90° Flag Terminal
AWG 20-18/16-14
0.5-1/1.5-2.5 mm²



KC-8FL1
For Tab 90° Flag Terminal
AWG 20-18
0.5-1 mm²



KC-8FL2
For Tab 90° Flag Terminal
AWG 16-14
1.5-2.5 mm²



KC-8FL03
For Insulated 90° Flag Terminal
AWG 20-18/16-14
0.5-1/1.5-2.5 mm²



KC-8FL09
For Insulated 90° Flag Terminal
AWG 10
6 mm²

Ratchet Hand Crimping Pliers KC-8 Series

Model	For Terminal	Application Range		Weight Kg.	Length mm.
		mm ²	AWG		
KC-8FL02	For Non-Insulated 90° Flag Terminal	0.5-1/1.5-2.5	20-18/16-14	0.6	230
KC-8FL1	Tab 90° Flag Terminal	0.5-1	20-18	0.6	230
KC-8FL2		1.5-2.5	16-14	0.6	230
KC-8FL03	For Insulated 90° Flag Terminal	0.5-1/1.5-2.5	20-18/16-14	0.6	230
KC-8FL09		6	10	0.6	230

