

TM-120
*Adjusting the top screw to change the crimping
For Non-Insulated Terminal*



TM-150
*Adjusting the top screw to change the crimping
For Non-Insulated Terminal*

คีมย้ำหางปลาเปลี่ยนแบบจิกรอยบาก

Model	Application Range			Weight Kg.	Length mm.
	JIS mm ²	DIN mm ²	AWG/MCM		
TM-120	8 - 100	10 - 120	8 - 250	3.20	570
TM-150	8 - 120	10 - 150	8 - 350	4.00	650




MH-125
For Close End Terminal



คีมย้ำหัวหมวก (Close End)

Model	Standard	Crimping Range			Weight Kg.	Length mm.
		0.5-1.5	1.5-2.5	4-6		
MH-125	DIN/JIS(mm ²)	0.5-1.5	1.5-2.5	4-6	0.30	180
	NEMA(AWG)	20-16	16-14	12-10		



HSC8-6-4A
For End Sleeves Terminal



คีมย้ำสลีปเข้าปลายสาย (End Sleeves Terminal)

Model	Application Range		Weight Kg.	Length mm.
	end sleeves	twin end sleeves		
HSC8-6-4A	0.08-6mm ²	2x0.2 - 2x4mm ²	0.39	175

